

**Hansun Engineering Co., Ltd.**

Busan

South Korea

Declaration

Kiwa Nederland B.V. hereby declares that the  
**CNG, Bleed valve series SBLV**  
**CNG, Purge valve series SPUV**

Described in annex to this certificate complies with the ISO15500:

Part 1 General Requirements

Part 2 General Test methods

Part 19 Fitting

Paul Dijkhof,  
Project Manager Automotive Systems



Appendix to declaration no. 126838MECH102

Appendix no.: 1  
Dated: 24 July 2014  
Examination report(s):  
126838 dated July 2014

Type break down (including specifications):

**Hansun Engineering Co., Ltd. Bleed valve series SBLV and Purge valve series SPUV**

Make(s):	Hansun Engineering Co., Ltd
Type(s):	Bleed valve series SPUV Purge valve series SBLV
Approval number(s):	ISO15500: 126838MECH102 NGV3.1: 126838AUT13
Declaration number(s):	R110 126838 Ext.:00
Working pressure:	R110: 26 MPa (Class 0) ISO 15500: 26 MPa NGV3.1 24.8 MPa (3600Psi)
Temperature range:	-40°C up to 120°C (-40°F up to 248°F)
Material(s)	Stainless steel (ASTM A276/479 TP316/316L)
Possible connections:	Tube O.D: Metric: 6mm~12mm Inch: 1/8" ~ 1/2" Pipe Thread: 1/8" ~ 1/2"